

## Overview

SW-218II sub-woofer speaker cabinet contains cuboid cabinet and long stroke woofer driver. It could be combined with all ranges of ENEWAVE full range speaker cabinets.

## Features

- \* Low distortion and high SPL output
- \* Reinforced component gets high powered capacity and well heat dispersion
- \* Strong Baltic birch plywood cabinet and coating by waterborne anti-scratch paint
- \* Stack installation is available
- \* DSP control technology



## Applications

### Apply to:

Touring system  
Lecture hall  
Bar  
Small and medium theater, auditorium  
Music hall  
Night club, KTV  
Social club  
Church

## Description

Almighty SW series is focused for combining with all ranges of ENEWAVE full range speaker cabinets. Pass through the advanced DSP control technology, SW series could be supported HLA,VLA,VA,Lark and Shrike series cabinets and extended bass till incredible 28Hz. It will increase more punch for entire sound system. SW-218II is a flat sub-woofer speaker with bass reflex technology. By using computer to pre-calculated and analysis cabinet resonance and then improve structure to reduce related resonance. Finally the bass tone will be clean and efficiency without any resonant noise. Optimize chamber designing is also reduced more dimension. The long stroke woofer speaker combines with advanced DSP control technology to efficient control over load

and distortion and bottoming noise during high power range. The durable cabinet was made by Baltic birth plywood and mortise joint technology. It offers transported handle on both side and reserved screw holes for wheels on back side for easy moving and transportation.

The coating is made by waterborne anti-scratch paint to achieve strong, reliability and environmental. SW-118II can perform unbelievable 28Hz to 2KHz frequency responsible and 99 dB(1m/1W) sensitivity, 138dB max. SPL. Therefore, it will be applying to conference room, classroom, church, outdoor, banquet hall, theater, auditorium, night club and so on.

## Technical Specifications

Performance Parameters	
Components	2 x 18" Neodymium woofer driver
Operating Type	Sub-Woofer speaker cabinet passive and driven by ext. amplifier
Profile	Cuboid
Cabinet	Baltic birch plywood
Surface	Waterborne anti-scratch paint
Connector	2 x NL4 Speakon
System Collocation	All of ENEWAVE full range cabinets
Dimension	567mm×1066mm×780mm(H×W×D)
Weight	87kg
Nominal Parameters	
Frequency Responsible	35Hz~500Hz (±3dB) 28Hz~2KHz (-10dB)
Sensitivity(1m/1W)	99dB
Nominal Impedance	4Ω
Rated Power(AES)	2000W Continue; 4000W Program; 8000W Peak;
Maximum SPL(1m)	138dB
Nominal Coverage Angel(-6dB)	N/A

## Dimension and diagram

Unit : mm

